

TECHNICAL DATA SHEET DATED: AUG 2023

903 Filmic Application Tape

903 is a clear polyethylene film coated with an acrylic adhesive specifically designed to transfer small to medium sized vinyl graphics. The plasticiser resistant adhesive guarantees a strong initial tack to all types of vinyl films.

The adhesive is coated in a way to ensure easy unrolling and elimination of static. The transparent film conforms well to irregular surfaces to enable accurate positioning.

Suitable for dry applications only. Easily removable after application.

PROPERTIES

Material:

Type: Filmic Application Tape
Face Film: Low density Polyethylene

Thickness: 110μ +/- 10% Colour: Transparent Dimension Stability: <0.5mm

Adhesive: Modified Acrylic

Adhesion to Steel: >3N / 25mm (20 minutes 180°C)

Application Temperature: +10°C - +40°C

OTHER INFORMATION

Storage:

Under normal conditions - ie: 50% relative humidity and room temperature of approx. 20°C this product in its original packaging can be stored for up to 6 months.

Notes

We recommend that the customer test the suitability of the product for the required purposes under original conditions.

The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship.

Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

Please contact us if you require any further information