

Double-sided Tape 4402

This hand tear-able cloth tape is coated with a modified acrylic adhesive and offers high initial tack and semi-permanent adhesion. This product is mostly plasticiser stable, has good resistance to aging and is solvent free. Suitable as a mounting tape for the print industry as well as for fixing carpet & PVC flooring.

PROPERTIES

Material:

Type:	Double-sided tape
Adhesive:	Modified acrylic, pressure sensitive
Carrier:	Woven fabric
Liner:	White silicone paper—120gsm
Thickness:	0.3mm—0.35mm
Application Temp:	18°C - 25°C
Temperature range:	-20°C - 100°C
Peel Adhesion (PSTC-1):	8N / 25mm x 25mm
Shear Resistance (PSTC-7):	>5 hours - 1kg / 25mm x 25mm

OTHER INFORMATION

Processing:

To obtain optimum adhesion the bonding surfaces must be dry and made clean of any dirt, dust and grease by using Isopropyl Alcohol. Observe recommended tape application temperatures and avoid touching the exposed adhesive surface. Use sufficient pressure over the whole surface to ensure maximum adhesive contact.

Storage:

Under normal conditions - ie: 50% relative humidity and room temperature of approx. 20°C this product in its original packaging can be stored for up to 6 months.

Notes:

We recommend that the customer test the suitability of the product for the required purposes under original conditions.

The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship.

Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

Please contact us if you require any further information