

WhiteboardMatt ASLAN WB 975

The white, matt and flexible whiteboard film

The white matt self-adhesive film is ideal for the creation of non-reflective whiteboards. It can be applied on every smooth surface and is perfect to use in seminar rooms, schools, restaurants, hospitals and many places more. The highly scratch-resistant surface avoids any shadows or ghost-writings. Writings can be wiped off easily with a microfibre cloth.

The non-reflective surface of the film is perfectly designed for front projections.

ASLAN recommends the use of whiteboard-markers.

For any further information please contact our technical advisory service:
+49 (0)2204.708-80

Construction

face-film:	Smooth PVC, white matt with special lacquering	
thickness:	~ 80 µm	
adhesive:	acrylic pressure sensitive adhesive	thickness: ~ 25 g/m ²
release liner:	silicone cardboard	square weight: ~ 144 g/m ²

Characteristics

adhesive strength: (ASTMD-903)	immediately after 1 week	~ 8 N/25 mm ~ 10 N/25 mm
dimensional stability:	applied onto aluminum after 48 hours stored at 70 °C (25 x 25 cm)	max. -0.2 %
chemical resistance:	In a preece test of 24 hours the applied film is resistant to most petroleum based oils, greases and aliphatic solvents, mild acids, alkaline and salts.	
temperature:	application temperature: service temperature range:	min. 15°C -30 °C up to +80 °C

ASLAN, Schwarz GmbH & Co. KG

Postfach 5165 · 51486 Overath · Oberauel 2 · 51491 Overath

fon +49 (0) 22 04. 7 08-80 · **fax** +49 (0) 22 04. 7 08-50 ·

e-mail info@ASLAN-schwarz.com

www.ASLAN-schwarz.com

ASLAN®
EXPERTISE IN SELF-ADHESIVE FILMS

WhiteboardMatt **ASLAN WB 975**

Processing

application:

The film can be applied dry or wet. A possible whitening of the adhesive if applied wet will disappear after a few days' time, depending on the weather conditions. For wet applications we recommend our transfer liquid ASLAN TL 10. For the application of letterings etc. we recommend our ASLAN application tapes respectively the ASLAN TMO.

Usage

For writings on the film any customary whiteboard marker can be used. We recommend a microfibre cloth to wipe off the writing. Writings with non-suitable pens (i.e. permanent markers) can be removed with alcohol or white gas.

storage life:

Before application the films can be stored at least 3 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed 'hanging' racks.

State: 09|2013

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test our products suitability for the purpose intended.

The quality of our products is regularly examined, upgraded and developed. We reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of their products in accordance with their latest knowledge.

ASLAN, Schwarz GmbH & Co. KG

Postfach 5165 · 51486 Overath · Oberauel 2 · 51491 Overath

fon +49 (0) 22 04. 7 08-80 · **fax** +49 (0) 22 04. 7 08-50 ·

e-mail info@ASLAN-schwarz.com

www.ASLAN-schwarz.com

ASLAN® 
EXPERTISE IN SELF-ADHESIVE FILMS