



MAGNETIC SHEETING

Frequently asked questions and answers on the care and application of magnetic sheeting.

Q Do the vehicles need special preparation before applying magnetic sheeting?

A Both the vehicle surface and the brown magnetic side of the sign should be clean, dry and waxed prior to application.

Q What is the best way to apply a magnetic sign?

A Let one edge of the sign contact the vehicle in the desired position, then let the magnet contact the vehicle positioning itself in the correct position from the original edge to the opposite. If the sign is not in the correct position, peel it off reposition the starting edge and repeat.

Make sure that the entire surface of the sign is smoothly against the vehicle with no air pockets, wrinkles or bumps which might catch the wind, especially under the forward facing edge. In winter the temperature of the sign should be about 50 degrees F during application, however the temperature of the vehicle doesn't matter.

Q Do any surfaces present problems?

A Care should be taken with wood grain panelling and metallic finishes, such surfaces should be checked weekly for the first 90 days of use. A generous waxing of both surfaces, both the back of the sign and where it will be placed will help to prevent any damage. Re-painted vehicle surfaces and those of new cars should be avoided for a minimum three months and must be hand wax polished before the sign is to be fitted to seal the surface. Remove frequently to allow the natural ultra violet light of the sun to evenly bleach the vehicle panels.

Q What sign maintenance is recommended?

A Remove the sign at least once a week and wipe dry both the magnetic side and the surface of the vehicle. This will keep the moisture from collecting, which can potentially damage a vehicle's surface. Simply wash it with warm water and mild detergent. Avoid cleaning fluids, petrol, acetone, benzene and chlorinated solvents. Remove Road film and any dirt before applying or re-applying the sign to the vehicle. **Make sure that the sign is removed after rain, sleet or snow and wiped dry, as moisture collecting behind the sign may damage the sign and possibly the vehicle if left unchecked.**

Q What special precautions must be taken in storing signs?

A Avoid wrinkling by storing in a 3" diameter roll with the printed side of the sign pointed to the outside of the roll, or store the sign flat. Since the magnetic sheet is permanently magnetic, you do not need to protect it against magnetic destruction. Don't put heavy objects on it or leaning up against it while in storage. During cold weather allow the sign to uncurl in a warm atmosphere.

Q Any other tips or suggestions?

A Corner rounding prevents dog-eared corners. Custom shapes should try to utilise rounded corners rather than sharp angles for the best results. You can use a cool iron to remove any accidental wrinkles you may put in the material.

THERE IS NO WARRANTY EXPRESSED OR IMPLIED AGAINST LOSS OF SIGN OR DAMAGE TO VEHICLE SURFACES, AS THE MANUFACTURER HAS NO CONTROL OVER HOW SIGNS ARE CARED FOR, ALTERED, STORED, AND/OR USED, OR THE SURFACE TO WHICH THE SIGNS ARE APPLIED.