



dorotape

Technical Data Sheet

950A Mounting Adhesive

A thin (12 μ) clear polyester film coated on both sides with a highly oxidative, UV and blanch resistant permanent acrylic adhesive which provides initial repositionability properties. The 120gsm PE coated liner is highly moisture stable and enables smooth unwinding characteristics. Typically used to mount inkjet printed photo quality posters and graphics to substrates such as foamed PVC, aluminium composite and card.

Base Material	Clear Polyester Film
Thickness (μ)	12 μ
Adhesive	Permanent acrylic on both sides
Adhesive Thickness (μ)	22 μ (on each side)
Release Liner	120gsm PE Coated 2 sided release liner
Application Temperature	10°C - 40°C
Service Temperature	-20°C - 70°C

Storage	Under normal conditions - ie: 50% relative humidity and room temperature of aprox 20°C this product in its original packaging can be stored for up to 6 months.
Note	The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship. We recommend that the customer test the suitability of the product for the required purposes under original conditions.

Please contact us if you would like any further information.

Doro Tape (UK) Ltd
New Mill
Farndon Road
Market Harborough
Leicestershire
LE16 9NP

Tel: 01858 431642
Fax: 01858 466992
Email: sales@dorotape.co.uk