



Laminates

All Purpose laminate with a solvent acrylic adhesive. Suitable for indoor & outdoor graphic applications to enhance and protect digitally printed images on a wide range of substrates. Available in Gloss, Lustre (Semi Matt) & Crystal Matt.

PROPERTIES

Material:

Type: Calendared monomeric PVC
Thickness: 100µm

Adhesive:

Formulation: Permanent solvent acrylic
Thickness: >22µ
Peel Strength: 13-15N/25mm (after 20 minutes on stainless steel)

Liner:

Release paper: Single sided PE coated silicone paper
Release paper weight: 100 g/m²

Application Temperature: Min +5°C

OTHER INFORMATION

Processing:

After printing, we recommend waiting at least 24 hours before applying laminates to ensure outgassing of any solvents. Always apply the material on to flat surfaces that are free of dirt and grease. We advise to check the compatibility between surface and adhesive before application.

Storage:

Under normal conditions - ie: 50% relative humidity and room temperature of approx. 20°C this product in its original packaging can be stored for up to 6 months.

Notes:

We recommend that the customer test the suitability of the product for the required purposes under original conditions. The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

Please contact us if you require any further information