

TECHNICAL DATA SHEET DATED: AUG 2023

D-Jet 200

This superb white gloss semi rigid vinyl has a very high tack permanent adhesive. It is ideal for use on flat surfaces and because of its thickness it is extremely easy to apply. The high tack adhesive bonds well to most substrates making this a popular choice for Health & Safety signage and POS.

PROPERTIES

Material:

Type: Monomeric soft PVC film

Colour: White gloss Thickness: 180µm

Adhesive:

Formulation: Copolymeric acrylates, solvent free, excellent resistance to UV light and ageing.

Complies with EN71/3 (application on toys)

Peel Adhesion: 14N / 25mm—20 minutes (FTM 1 on glass)

19N / 25mm-24 hours (FTM 1 on glass)

Application Temperature: Min +5°C Service Temperature: -30°C - +90°C Outdoor Durability: 2-3 Years

Ink Compatibility: Eco Solvent, Solvent, Latex & UV

OTHER INFORMATION

Processing:

After printing, we recommend waiting at least 24 hours before applying to ensure outgassing of any solvents.

Always apply the material on to flat surfaces that are free of dirt and grease. We advise to check the compatibility between surface and adhesive before application.

Storage:

Under normal conditions - ie: 50% relative humidity and room temperature of approx. 20°C this product in its original packaging can be stored for up to 6 months.

Notes:

We recommend that the customer test the suitability of the product for the required purposes under original conditions.

The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship.

Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

Please contact us if you require any further information