

Digi-Banner 440

A low cost super smooth 440gsm banner pvc designed to maximise ink adhesion and colour reproduction. Ideal for low cost digitally printed banner for use both internally and low stress external use.

PROPERTIES

Material:

Type:	Trade mark polyester (DIN 60001)
Coating:	PVC Lamination
Thickness (mm):	0.42 +/- 0.02
Warp/Welt:	300d x 500d
Threads per inch:	10/12 (DIN 53853)
Total Weight:	440gsm +/- 20gsm (DIN 53352)
Tensile Strength:	450 / 400 N/30mm (DIN 53354)
Tear Resistance:	100 / 150 N/30mm (DIN 53363)

Ink Compatibility: Eco Solvent, Solvent, Latex & UV

Flame Retardant: Self Extinguishing (DIN 75200)

OTHER INFORMATION

Processing:

After printing, we recommend waiting at least 24 hours before applying to ensure outgassing of any solvents.

Storage:

Under normal conditions - ie: 50% relative humidity and room temperature of approx. 20°C this product in its original packaging can be stored for up to 6 months.

Notes:

We recommend that the customer test the suitability of the product for the required purposes under original conditions.

The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship.

Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

Please contact us if you require any further information

Doro Tape (UK) Ltd, New Mill, Farndon Road, Market Harborough, LE16 9NP

Tel: 01858 431642 Email: sales@dorotape.co.uk