

## Digi-Banner Blockout

A very smooth satin coated banner material with a black middle layer for complete opacity making it ideal for printing high resolution double sided banners.

### PROPERTIES

**Material:**

Type: Trade mark polyester (DIN 60001)

Coating: PVC Coating

Warp/Welt: 500d x 500d

Threads per inch: 28 / 28

Total Weight: 610gsm +/- 20gsm (DIN 53352)

Ink Compatibility: Eco Solvent, Solvent, Latex & UV

Flame Retardant: Self Extinguishing (DIN 75200)

### OTHER INFORMATION

**Processing:**

After printing, we recommend waiting at least 24 hours before applying to ensure outgassing of any solvents.

**Storage:**

Under normal conditions - ie: 50% relative humidity and room temperature of approx. 20°C this product in its original packaging can be stored for up to 6 months.

**Notes:**

We recommend that the customer test the suitability of the product for the required purposes under original conditions.

The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship.

Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

**Please contact us if you require any further information**