

## Double-sided Tape 470

The rigid PVC base has a heavy duty solvent acrylic adhesive giving it excellent holding power and adhesion as well as good resistance to UV, plasticisers and ageing. Suitable for plasticised PVC and numerous fixing, mounting and assembly applications.

### PROPERTIES

**Material:**

Type:	Double-sided tape
Adhesive:	Cross linked, High performance solvent acrylic, pressure sensitive
Carrier:	White PVC—0.06mm
Liner:	Havana brown glassine paper—80gsm
Thickness:	0.21mm—0.215mm
Application Temp:	18°C - 25°C
Temperature range:	-20°C - 90°C
Peel Adhesion (PSTC-1):	2400g / 25mm x 25mm
Shear Resistance (PSTC-7):	>24hrs – 1kg / 25mm x 25mm
Solvent Resistance:	Good

### OTHER INFORMATION

**Processing:**

To obtain optimum adhesion the bonding surfaces must be dry and made clean of any dirt, dust and grease by using Isopropyl Alcohol. Observe recommended tape application temperatures and avoid touching the exposed adhesive surface. Use sufficient pressure over the whole surface to ensure maximum adhesive contact.

**Storage:**

Under normal conditions - ie: 50% relative humidity and room temperature of approx. 20°C this product in its original packaging can be stored for up to 6 months.

**Notes:**

We recommend that the customer test the suitability of the product for the required purposes under original conditions.

The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship.

Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

**Please contact us if you require any further information**