

Double-sided Tape 866

This pressure sensitive double-sided white foam tape with a solvent acrylic adhesive is suitable for interior as well as exterior applications and combines high initial tack with good cohesion and adhesion. Suitable for use on moderately uneven surfaces.

PROPERTIES

Material:

Type:	Double-sided tape
Adhesive:	High performance solvent acrylic, pressure sensitive (transparent)
Carrier:	Closed cell white PE foam—density 96kg/m ³
Liner:	White PE paper—110gsm
Thickness:	0.8mm—0.85mm
Application Temp:	18°C - 25°C
Temperature range:	-20°C - 80°C
Peel Adhesion (PSTC-1):	19.5N / 25mm x 25mm
Shear Resistance (PSTC-7):	>24hrs – 0.5kg / 25mm x 25mm
Solvent Resistance:	Good

OTHER INFORMATION

Processing:

To obtain optimum adhesion the bonding surfaces must be dry and made clean of any dirt, dust and grease by using Isopropyl Alcohol. Observe recommended tape application temperatures and avoid touching the exposed adhesive surface. Use sufficient pressure over the whole surface to ensure maximum adhesive contact.

Storage:

Under normal conditions - ie: 50% relative humidity and room temperature of approx. 20°C this product in its original packaging can be stored for up to 6 months.

Notes:

We recommend that the customer test the suitability of the product for the required purposes under original conditions.

The technical information given here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship.

Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

Please contact us if you require any further information