

VISCOM-RI-MARK - SOFT VINYLs

Issue date : 05/01/2005
Date last modification : 01/10/2013**03529 ETCH GLASS PTA/PTAS/PTB/PTF SERIES ASP26 PERMANENT WK120****Face Material**

Self-adhesive material for plotter. Polymeric translucent vinyl with metallic flakes.

Type	Translucent polymeric vinyl	
Colour and Finish	4 colours available	
Weight	100 g/m ² ±10%	ISO-536
Thickness	80 µ ±10%	ISO 534-80

Adhesive

Permanent solvent acrylic featuring high cohesion and good water resistance.

Reference	ASP26 permanent	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-20°C/+130°C	
Shear	High	
Tack	Medium N/inch ²	
Final Adhesion	High N/inch	

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	120 g/m ² ±10%	ISO 536
Thickness	108 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Translucent Etch simulation effect for glass decoration. 5 years outdoor durability. Durability is given in good faith based on simulated weathering tests and real life vertical exposure in non-extreme mid-European conditions.

Printing Methods

Not printable.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

